

# PPC-Ci215-N7091

Intel® 6<sup>th</sup> Generation Core™ i7/ i5/ i3/ Xeon® E3-1200v5 Socket 1151 Desktop Processor Q236 Chipset Based 21.5" LCD Panel PC with 4 USB 2.0/ 6 USB 3.0/ 6x COM Ports/ DVI/Dual Gigabit LAN



## FEATURES

- Intel® 6<sup>th</sup> Generation Core™ i7/ i5/ i3/ Xeon® E3-1200v5 Desktop socket 1151
- Intel® Q236 Express chipset
- Two DDR4 DIMM 1866 / 2133 MHz up to 32GB
- One Intel® I210 Gigabit LAN and 1 x Intel® I219-LM Gigabit PHY LAN
- Intel® Core™ integrated HD Graphics 530 Technology
- Realtek® ALC262 High-Definition Audio chip on-board
- Multi I/O: 4x USB 2.0, 6x USB 3.0, 6x COM ports, 4x SATA
- Expansion: PCIe x16 slot, 1x Mini-PCIe socket & 1x Half Size Mini PCIe socket
- Bay: 1x Slim SATA DVDRW, 2x 2.5" HDD (Internal) Bays

## Introduction

PPC-Ci215-N7091 Industrial Panel PC supporting Intel® 6<sup>th</sup> Generation Intel® Skylake™ i7 / i5 / i3 series and Xeon® E3-1200 v5 Desktop Processor. PPC-Ci215-N7091 comes with 21.5" LCD Display. PPC-Ci215X-N7091 supports one Slim DVDRW and Two 2.5" Hard Disk, 6x COM Port, 4 x USB 2.0, 6 x USB 3.0 and one PCIe x16 expansion slot.

PPC-Ci215-N7091 is ideal for developing high-performance systems for industrial control and Automation, retail, gaming, print imaging and digital signage.

## Specification

Model	PPC-Ci215-N7091
<b>LCD</b>	
Resolution	FHD 1920x1080
Brightness	300 cd/m <sup>2</sup>
Contrast Ratio	5000:1
Viewing Angle	178/178
Backlight	LED
Backlight MTBF	30000Hrs
<b>System</b>	
Processor	<ul style="list-style-type: none"> <li>• 6<sup>th</sup> Generation Intel® Skylake™ i7 / i5 / i3 series and Xeon® E3-1200 v5 Desktop Processor.</li> <li>- Intel® Core™ i7-6700T Processor (8M Cache, up to 3.60 GHz)</li> <li>- Intel® Core™ i5-6600T Processor (6M Cache, up to 3.50 GHz)</li> <li>- Intel® Core™ i3-6300T Processor (4M Cache, 3.30 GHz)</li> <li>- Intel® Xeon® Processor E3-1275 v5 (8M Cache, 3.60 GHz)</li> <li>• Package Type: FCLGA1151</li> </ul>
BIOS	<ul style="list-style-type: none"> <li>• uEFI BIOS. 64Mbit FlashROM with DOS and Windows update utility support.</li> </ul>
System Memory	<ul style="list-style-type: none"> <li>• Two DDR4 1866/2133 Mhz DIMM Module up to 32GB</li> <li>• Supports Non ECC Memory only</li> </ul>
Chipset	<ul style="list-style-type: none"> <li>• Intel® Q236 Express chipset</li> </ul>
Video	<ul style="list-style-type: none"> <li>• Intel® Core™ integrated HD Graphics 530 Technology</li> <li>• Onboard 15-pin CRT interface</li> <li>• Onboard DVI connector</li> <li>• Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply</li> <li>• Onboard Display port connector</li> </ul>
Ethernet	<ul style="list-style-type: none"> <li>• One Intel® I210 Gigabit LAN and 1 x Intel® I219-LM Gigabit PHY LAN</li> <li>• Support Wake-on-LAN, Remote Boot with PXE and RTL.</li> </ul>
On Board I/O	<ul style="list-style-type: none"> <li>• Four serial ports as COM1~COM6. One COM Port is RS232/422/485 selectable by jumper with auto-flow control.</li> <li>• Four SATA-III ports (Support RAID 0, 1, 5, 10 and Intel Rapid Storage Technology.)</li> <li>• Support Six USB3.0 ports. Four ports are on rear I/O.</li> <li>• Support Four USB2.0 ports. Two ports are on rear I/O.</li> <li>• 8bits Digital I/O</li> <li>• One SMBus interface</li> <li>• PS2 KB and MS. (Optional)</li> </ul>
Watchdog Timer	<ul style="list-style-type: none"> <li>• Programmable watchdog timer for 1~255 seconds.</li> </ul>
CMOS	<ul style="list-style-type: none"> <li>• On-board RTC with 242 bytes of Battery-back CMOS RAM.</li> </ul>
Audio	<ul style="list-style-type: none"> <li>• RealTek® ALC262 High-Definition Audio chip on-board.</li> <li>• Support Line-in, MIC-in, Front, Rear, Center/Subwoofer</li> </ul>
TPM	<ul style="list-style-type: none"> <li>• Infineon TPM 1.2 on board supports security functions</li> </ul>
Power	<ul style="list-style-type: none"> <li>• Standard 20Pin + 4pin ATX power supply</li> <li>• Support both AT and ATX mode.</li> </ul>
<b>Power Requirement</b>	
Power Supply	<ul style="list-style-type: none"> <li>• Industrial Auto Range 300W Power Supply</li> </ul>
<b>Mechanical &amp; Environment</b>	
Drive Bay	<ul style="list-style-type: none"> <li>• One Slim DVDRW &amp; Two 2.5" Hard Disk Bays</li> </ul>
Dimension	<ul style="list-style-type: none"> <li>• 551.65(W) x 343(H) x 113(D) mm</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• Gross 18kg</li> </ul>
Operation temperature	<ul style="list-style-type: none"> <li>• 0°C to 60°C (32° F to 140° F)</li> </ul>
Storage temperature	<ul style="list-style-type: none"> <li>• -20°C to 80°C (-68° F to 176° F)</li> </ul>
Relative humidity	<ul style="list-style-type: none"> <li>• 5% to 95% (Non-Condensing)</li> </ul>
Additional Chassis FAN	<ul style="list-style-type: none"> <li>• 2x 40mm</li> </ul>
Front Bezel protection	<ul style="list-style-type: none"> <li>• IP65 Compliant</li> </ul>

## Ordering Information

PPC-Ci215-N7091-C100	Intel® 6 <sup>th</sup> Generation Intel® Skylake™ i7 / i5 / i3 series and Xeon® E3-1200 v5 Desktop Processor Q236 Chipset Based 21.5" LCD Panel PC 300cd/m <sup>2</sup> with 4 USB 2.0/6 USB 3.0/6x COM Ports/VGA /Dual Gigabit LAN, 300W Power Supply ARG Protection and Sensor & Slim Socket 1155 CPU Cooler
PPC-Ci215-N7091-C101	Intel® 6 <sup>th</sup> Generation Intel® Skylake™ i7 / i5 / i3 series and Xeon® E3-1200 v5 Desktop Processor Q236 Chipset Based 21.5" LCD Panel PC 300cd/m <sup>2</sup> with 4 USB 2.0/6 USB 3.0/6x COM Ports/VGA /Dual Gigabit LAN, 300W Power Supply/USB Touch Screen Controller and Sensor & Slim Socket 1155 CPU Cooler
PPC-Ci215-N7091-C102	Intel® 6 <sup>th</sup> Generation Intel® Skylake™ i7 / i5 / i3 series and Xeon® E3-1200 v5 Desktop Processor Q236 Chipset Based 21.5" LCD Panel PC 300cd/m <sup>2</sup> with 4 USB 2.0/6 USB 3.0/6x COM Ports/VGA /Dual Gigabit LAN, 300W Power Supply/RS-232 Touch Screen Controller and Sensor & Slim Socket 1155 CPU Cooler

## Dimension

